



Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet

PN: SSA093C

Last Update: 08/14/26

Page 1 of 21

© 2026 All Rights Reserved

PN: SSA093C




X Band Antenna

Hemispherical Coverage

TRL 9

Mass: 96g



Features

- **Radiation Pattern with Rectangular Form Factor**
First approximation for an “isoflux” pattern, see page 3
- **Proprietary Ultra-Compact All-Metal Polarizer**
Approximately 50 mm
- **Low Insertion Loss**
No internal gaps or joints in the central waveguide
- **Low Back Radiation Level**
High front-to-back ratio across the entire data downlink bandwidth 8.0-8.4 GHz






Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C

Page 2 of 21

© 2026 All Rights Reserved



Benefits

- **Designed for assembly, automation suitability, and optimal cost-effectiveness for high production batches**

Suitable for high-reliability data downlink service in satellite constellations, earth observation missions, or exploration probes

- **High power handling and a very compact LGA Channel solution**

Ideal for high bit rate communications. Only 60mm in diameter

- **Lossless by design**

No hidden coupling power exists through the Cross Polarization Port, unlike the Septum Polarizer

- **No performance degradation at end-of-life by design**

Without a dielectric or ceramic-loaded waveguide, sensitivity to space ionizing radiation and temperature is not an issue





Standard Space Antennas


SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C

Page 3 of 21


© 2026 All Rights Reserved

Models



Polarizer

SSA093A



SSA093B




SSA093C

VSWR

Verification by Simulation of VSWR @ PN: SSA093 Models A, B & C


Frequency: [8.0:8.4] GHz, Method: Full Wave Simulation, Boundary Conditions: Isolated Antenna



Pattern Formation Process

Verification by Simulation of RHCP Gain Pattern @ Boresight - PN: SSA093 Models A, B & C

Frequency: 8.2 GHz, $\theta = [-180; 180]$ deg, $\phi = 0$ deg, Method: Full Wave Simulation, Boundary Conditions: Isolated Antenna





Standard Space Antennas



SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C

Page 4 of 21

© 2026 All Rights Reserved

Mechanical Envelope





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C

Page 5 of 21

© 2026 All Rights Reserved

Typical Specifications @ Isolated condition

Parameter	Values	Remark
Frequency Range [GHz]	8.025 – 8.4	
VSWR	1.2	Worst Case @ Frequency Range [AD 12]
Bandwidth @ VSWR = 1.2 [GHz]	8 – 8.4 GHz	Antenna Bandwidth [AD 12]
Port to Port Isolation [dB]	NA	Single Port
Radiation Efficiency [%]	96.4	@ Frequency Range, Assuming a 3% degradation from expected [AD 10]
Total Efficiency [%]	95.7	@ Frequency Range, Assuming a 3% degradation from expected [AD 10]
Radiation Pattern Envelope	Sectoral	Rectangular Form Factor (First Approximation)
Phase Center [mm]	X= 0 ; Y= 0 ; Z= 31	Relative to Antenna Coordinated System. Z=0 $\equiv$ Mounting Joint Surface
Gain @ End of Coverage [dBi]	> 1.5	RHCP @ theta= 60°. [AD 4]
HPBW [°]	~105	@ Frequency Range, [AD 2]
Polarization Sense	Circular	RHCP
Polarization Ratio [dB] Worst Case	10.8 @theta < 60°	@ Frequency Range. [AD 4]
Multipath Ratio [dB] Worst Case Ref: $G_{RHCP}(\theta)/G_{LHCP}(180-\theta)$	12.7 @theta < 60°	@ Frequency Range. [AD 4]
Multipactor Margin [dB]	> 9	@ 70 W. Obtained via Aerospace Corporation Model Analysis, by Similarity with SSA071A
Corona Discharge Margin [dB]	NA	Non Operative during Launch





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C

Page 6 of 21

© 2026 All Rights Reserved

Enviromental Test & Mechanical Interface

Parameter	Values	Remark
Mass (g)	96	Center of Mass: [0.2, 0.2, 6.34] mm from Mounting Joint Surface ($\equiv Z=0$ of Antenna Coordinate System). [AD 1]
Size (mm)	59.2 (79)	Cavity Diameter (Max Envelope) [AD 1]
Height (mm)	46.6	Overall Height measured from Mounting Joint Surface. [AD 7] (Flush: 49.7 mm)
RF Interface	SMA Female	[AD1]
Electrostatic Discharge	ESD Free	Verified by Review of Design
Outgassing	TML < 1.00 % CVCM < 0.05%	According to Declared Material, Component and Processes List [AD 7]
Temperature Range [°C]	Ref 1: (-105; 125) °C Ref 2: (-70, 100) °C	Ref 1: Thermal Vacuum Test, Four Cycles, 2 hours Dwell. [AD 8] Ref 2: Thermal Vacuum Test, Eight Cycles, 4 hours Dwell. [AD 2] (Heritage by Similarity with SSA071A)
Vacuum [Hpa]	$\leq 1.33 \times 10^{-5} \pm 80\%$	In Thermal Vacuum Test [AD 8]
1st Natural Frequency [Hz]	1644	Analysis in [AD 11] Success with several Mast and Bracket Configuration [AD 2]. Numerical versus Test Deviation < 4%
Dynamic Acceleracion Loads [Grms]	20 - 50 Hz: +6 dB/oct 50 - 70 Hz: 0.16 g ² /Hz 70 - 80 Hz: +6 dB/oct 80 - 350 Hz: 0.2 g ² /Hz 350 - 400 Hz: -6 dB/oct 400 - 800 Hz: 0.16 g ² /Hz 800 - 2000 Hz: -6 dB/oct <u>Overall: 14.55</u>	Shaker Test @ Random Vibration, Three Axis, 2 min / axis [AD 2]. Success with several Mast and Bracket Configuration (Heritage by Similarity with SSA071A) Verified by Analysis in [AD 5]
Static Acceleration Loads [G]	Peak: 65	Shaker Test @ Sine Burst, Three Axis [AD 2], Qualification Level





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 7 of 21

© 2026 All Rights Reserved

VSWR

Verification by Simulation of VSWR @ SSA093C

Frequency: [8:0.1:8.4] GHz, Method: Full Wave Simulation, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 8 of 21

© 2026 All Rights Reserved

Gain vs Frequency @ EoC ($\theta = 60^\circ$)

Verification by Simulation of RHCP Gain @ EoC - PN: SSA093C

Frequency: [8:0.1:8.4] GHz, $\theta = 60$ deg, $\phi = [0:5:360]$ deg, Method: Full Wave Simulation, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 9 of 21

© 2026 All Rights Reserved

Gain Pattern @ 8 GHz

Verification by Simulation of RHCP Gain Pattern - PN: SSA093C

Freq. 8.0 GHz, Method: Full Wave Simulation, $\theta = [0:1:90]$ deg, $\phi = [0:5:360]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 10 of 21

© 2026 All Rights Reserved

Gain Pattern @ 8.2 GHz

Verification by Simulation of RHCP Gain Pattern - PN: SSA093C

Freq. 8.2 GHz, Method: Full Wave Simulation, $\theta = [0:1:90]$ deg, $\phi = [0:5:360]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 11 of 21

© 2026 All Rights Reserved

Gain Pattern @ 8.4 GHz

Verification by Simulation of RHCP Gain Pattern - PN: SSA093C

Freq. 8.4 GHz, Method: Full Wave Simulation, $\theta = [0:1:90]$ deg, $\phi = [0:5:360]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 12 of 21

© 2026 All Rights Reserved

Radiation Pattern Principal Cuts @ 8.0 GHz

Verification by Simulation of RHCP & LHCP Radiation Pattern - PN: SSA093C

Principal Cuts, $\theta = [-180:1:180]$, $\phi = [0;90]$ deg, Freq. 8.0 GHz, Method: Full Wave Simulation, deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 13 of 21

© 2026 All Rights Reserved

Radiation Pattern Principal Cuts @ 8.2 GHz

Verification by Simulation of RHCP & LHCP Radiation Pattern - PN: SSA093C

Principal Cuts, $\theta = [-180:1:180]$, $\phi = [0;90]$ deg, Freq. 8.2 GHz, Method: Full Wave Simulation, deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 14 of 21

© 2026 All Rights Reserved

Radiation Pattern Principal Cuts @ 8.4 GHz

Verification by Simulation of RHCP & LHCP Radiation Pattern - PN: SSA093C

Principal Cuts, $\theta = [-180:1:180]$, $\phi = [0;90]$ deg, Freq. 8.4 GHz, Method: Full Wave Simulation, deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 15 of 21

© 2026 All Rights Reserved

Polarization Ratio Pattern @ 8 GHz

Verification by Simulation of Polarization Ratio Pattern - PN: SSA093C

Principal Cuts, $\phi = [0;90]\text{deg}$, Freq. 8 GHz, Method: Full Wave Simulation, $\theta = [-180:1:180]\text{deg}$, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 16 of 21

© 2026 All Rights Reserved

Polarization Ratio Pattern @ 8.2 GHz

Verification by Simulation of Polarization Ratio Pattern - PN: SSA093C

Principal Cuts, $\phi = [0;90]$ deg, Freq. 8.2 GHz, Method: Full Wave Simulation, $\theta = [-180:1:180]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 17 of 21

© 2026 All Rights Reserved

Polarization Ratio Pattern @ 8.4 GHz

Verification by Simulation of Polarization Ratio Pattern - PN: SSA093C

Principal Cuts, $\phi = [0;90]$ deg, Freq. 8.4 GHz, Method: Full Wave Simulation, $\theta = [-180:1:180]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 18 of 21

© 2026 All Rights Reserved

Multipath Ratio Pattern @ Frequency: 8 GHz

Verification by Simulation of Multipath Ratio - PN: SSA093C

Full Spherical Cuts, Freq. 8.0 GHz, $\theta = [0:1:90]$ deg, $\phi = [0:5:180]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 19 of 21

© 2026 All Rights Reserved

Multipath Ratio Pattern @ Frequency: 8.2 GHz

Verification by Simulation of Multipath Ratio - PN: SSA093C

Full Spherical Cuts, Freq. 8.2 GHz, $\theta = [0:1:90]$ deg, $\phi = [0:5:180]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C


Page 20 of 21

© 2026 All Rights Reserved

Multipath Ratio Pattern @ Frequency: 8.4 GHz

Verification by Simulation of Multipath Ratio - PN: SSA093C

Full Spherical Cuts, Freq. 8.4 GHz, $\theta = [0:1:90]$ deg, $\phi = [0:5:180]$ deg, Boundary Conditions: Isolated Antenna





Standard Space Antennas

SPACE-READY ANTENNAS, WHEN TIME AND RELIABILITY MATTER

Datasheet
PN: SSA093C

Page 21 of 21

© 2026 All Rights Reserved

Our Additional Services Include:

- **Installed Performance: Pattern Distortion, Coverage & Cosite Interference**
- **Full Functional Test**
- **Environmental Test: Shaker, Thermal vacuum**
- **Antenna Bracket Design & Supply**
- **Electrical Ground Support Equipment (Hat)**

Contact Us for More Information



**Keep the antenna
from deciding if
your mission is
successful.**



www.ssa-lab.com



info@ssa-lab.com



+1 (561) 806-4296



3651 FAU BLVD STE 400, Boca Raton, FL 33431